

AMERICAN SAW & MFG. COMPANY


301 CHESTNUT STREET, EAST LONGMEADOW, MA 01028 U.S.A.
 800/628-3030 • 413/525-3961
 FAX: 800/223-7906
 TELEX: 955-310 AMSAW ELGM

MATERIAL SAFETY DATA SHEET (MSDS)

HMIS INDEX

HEALTH - 0
 FLAMMABILITY - 0
 REACTIVITY - 0
 PERSONAL PROTECTION - A

NFPA CODE



SECTION I **EMERGENCY TELEPHONE NO.**

TRADE NAME (if None, Put Chemical) Lenox® Lube™ 413/525-3961 ext.608

CHEMICAL NAME AND SYNONYMS Cutting Lubricant **PREPARATION DATE** 6/3/91

MANUFACTURER'S NAME American Saw & Mfg. Company

ADDRESS (Number, Street, City, State, Zip Code) 301 Chestnut Street, East Longmeadow, MA 01028 U.S.A.

SECTION II - INGREDIENTS

HAZARDOUS Ingredients - None.

This Lubricant Does Not Contain Any Chemicals Listed In SARA III, Section 313 Of The Emergency Planning And Community Right-To-Know Act Of 1986 Or In OSHA 29 CFR 1910, Subpart Z list.

SECTION III - PHYSICAL DATA

BOILING POINT (°C) / (°F)	99°C / 210°F	PERCENT VOLATILE BY VOLUME (%)	NA
VAPOR PRESSURE (MM Hg.)	68°F	pH	8.0
VAPOR DENSITY (AIR=1)	Heavier Than Air	EVAPORATION RATE	NA
SOLUBILITY IN WATER	100%	FREEZING POINT (°C) / (°F)	-5°C / 23°F
SPECIFIC GRAVITY (H ₂ O=1)	0.99		

APPEARANCE AND ODOR Translucent Green Liquid, Wintergreen Odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used) None. **FLAMMABLE LIMITS** None **LEL** NA **UEL** NA

EXTINGUISHING MEDIA Water Or Carbon Dioxide.

SPECIAL FIRE FIGHTING PROCEDURES None Required.

UNUSUAL FIRE AND EXPLOSION HAZARDS None.

NA - Not Applicable

SECTION V - HEALTH HAZARD INFORMATION

SYMPTOMS/EFFECTS OF OVEREXPOSURE None Known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE None Known.

CARCINOGENICITY Non-Carcinogenic.

FIRST AID

EYES Flush Eyes With Water For 15 Minutes. See Physician If Irritation Persists.

SKIN Wash Affected Area With Soap And Water.

INGESTION Do Not Induce Vomiting. Contact A Physician As A Precautionary Measure.

SECTION VI - REACTIVITY DATA

STABILITY Product Is Stable And Will Not Polymerize.

INCOMPATIBLE MATERIALS Strong Acids Or Alkali.

HAZARDOUS DECOMPOSITION PRODUCTS None Known.

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES Small Amounts - Flush With Water. Large Amounts Should Be Removed And Disposed Of In Accordance With Local, State And Federal Regulations.

WASTE DISPOSAL METHOD Used Lubricant Must Be Disposed Of In Accordance With Local, State And Federal Regulations. Determine Waste Classification At Time Of Disposal. Conditions Of Use May Render This Material As Hazardous Waste.

SECTION VIII - SPECIAL PROTECTION INFORMATION

EYEWEAR Wear Eye Protection.

CLOTHING/GLOVES Wear Personal Protective Equipment As Needed, i.e. Gloves.

RESPIRATORY None Required.

VENTILATION Local Ventilation To Maintain Level At Less Than 5 mgm/m³ Air.

WORK/HYGIENIC PRACTICES Wash Hands With Soap And Water As Required.

SECTION IX - SPECIAL PRECAUTIONS

Use As Directed. Store Indoors.
Contaminated Clothing Should Be Washed Before Reuse.
For Industrial Use Only.
Protect From Freezing. If Frozen, Thaw To Room Temperature.

PREPARED BY Martin S. Kane
NAME

Director, Corporate Technology
TITLE

6/3/91
DATE

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.