

MSDS: WLD40C 01/01

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Dissolvo™ WLD40C and Dissolvo™ HS100C

MANUFACTURER: Gilbreth Packaging Systems
3001 State Road
Croydon, PA 19021

HAZARDOUS MATERIALS DESCRIPTION: Non restricted material
HAZARD CLASS: Non restricted material
CHEMICAL FAMILY: Cellulose derivative

INGREDIENTS: (by weight)

Carboxymethyl Cellulose	68%
Polyvinyl Acetate	15%
Wood Pulp Fibers	17%

PHYSICAL DATA:

Thickness	.005" thick
Basic Weight	72g/M ²
Solubility in Water	Excellent
Percent Volatile by Volume	N/A
Evaporation Rate	N/A
Appearance	Solid white colloidal suspension
Odor	None
Toxicity	Does not require cautionary labeling; not to be ingested
Auto-ignition Temperature	>500° F

REACTIVITY:

Incompatibility (Materials to Avoid)	None
Hazardous Decomposition Products	None
Hazardous Polymerization	Will not occur

WASTE DISPOSAL: Incinerate or water flush

NOTE: Small amounts dropped on a wet floor could be slippery and should be cleaned up immediately.

SPECIAL PROTECTION INFORMATION:

Respiratory Protection	None required
Local Exhaust Ventilation	None required
Protective Gloves	None required
Eye Protection	None required

NOTE: When using Dissolvo in conjunction with welding gases, it is necessary to observe the rules for the safe handling of compressed gas as outlined in the Compressed Gas Association Pamphlet P-1 (Section 4.6, page 12) "When using an inert gas for welding, a safe contained breathing apparatus or airline mask should be worn for safety".

STORAGE PRECAUTIONS:
Avoid water contact and prolonged exposure to high heat or direct sunlight. When not in use, keep sealed in original polyethylene wrapping and stored in a cardboard or other sturdy opaque container.